



TWIST TOP SHOWER SYSTEM

THE TWIST TOP SYSTEM HAS BEEN SPECIALLY DESIGNED TO CATER FOR THE REQUIREMENTS OF PLUMBERS, TILERS AND WATERPROOFERS. OUR RESEARCH AND DEVELOPMENT TEAM HAVE BEEN ABLE TO PROVIDE SOLUTIONS TO PROBLEMS, WHICH ARE BOTH ECONOMICAL AND PRACTICAL.

FLOOR GRATE

An extensive range of stubby floor wastes are available in round, octagonal, square ASA plastic and stainless steel. Round and square brass are also available in slotted and floral patterns. A tile kit is also available. The fitment of the floor grate permits 5 degrees of lateral movement to accommodate various tile gradients.

DUST COVER/TILE TEMPLATE

Dust covers are provided to prevent the entry of debris in the water system during construction. The dust cover also acts as a tile template.

STRAINER (OPTIONAL EXTRA)

Integral strainers are available in 80 and 100mm to suit the Twist Top range.

SUD SAVER (OPTIONAL EXTRA)

Integral sud savers are available in 80 and 100mm to suit the Twist Top range.

ADAPTOR

The adaptor and flange are connected by a patented thread to adjust the height of the floor grate to accommodate various thicknesses of the tile bed or permit a direct stick method of tiling, the recessed flange is the most suitable for tiling direct to timber or concrete floors.

FLANGE

Flanges can either be recessed or surface installed. The surface mounted flange requires no removal of concrete around the waste discharge pipe. A space has been created at the inlet of the flange to accommodate installation of a vertical waterproof membrane. The flange has a unique surface structure to promote adhesion of the waterproof membrane. There are two flange types and two spigot outlets available - Solvent weld, RRJ adjustable or threaded flange outlets.

