



PLASTEC

FLEXIBLE JOINTS

FLEXITEC

- Ideal for use as Flexible Joints as per AS2870 on unstable and reactive soil sites, but may be used in many applications where flexible plumbing is required.
- Ideal for sewer and stormwater installations.
- Suitable for above and below ground applications with either vertical or horizontal installation.
- Superior flexibility, angular deflection, rotation, expansion and compression.
- Superior resistance to fatigue, UV aging and general weathering.
- Ability to be used in temperatures ranging from -50°C to 120°C.
- Excellence resistance to acids, chemical detergents and cleaners.
- Solvent cement as per AS3500.



PRODUCT SPECIFICATIONS

MEASUREMENTS (MM)

Ø

- 18914 - 52.7mm
- 18852 - 66mm
- 18853 - 79.5mm
- 18854 - 93.7mm
- 17728 - 121.8mm
- 18732 - 173.3mm
- 18735 - 267.5mm

- 18914 - 165mm
- 18852 - 176mm
- 18853 - 192.4mm
- 18854 - 210mm
- 17728 - 228mm
- 18732 - 335.4mm
- 18735 - 509.2mm

Note: Contact Plastec prior to purchase for further information regarding installation in Trade Waste applications.

ID	Ø	INLET	OUTLET	BAG QTY	CARTON QTY	FINISH/COLOUR	MEASUREMENT (MM)
18914	40	Socket	Socket	95			
18852	50	Socket	Socket	58			
18853	65	Socket	Socket	60			
18854	80	Socket	Socket	43			
17728	100	Socket	Socket	22			
18732	150	Socket	Socket	6			
18735	225	Socket	Socket	2			



PH: 07 5413 4444 WWW.PLASTEC.COM.AU

DETAILS CORRECT AT TIME OF PRINTING (03.03.2017) BUT IS SUBJECT TO CHANGE